

Stretch Base

General

It is produced for printing on the floor.

Advantages

- Stretch Base has been improved for high wash and it has extremely wash fastness.
- It can be printed to elastic base.
- It is fixed under room temperature and provides soft printings.
- Suitable to ecological standards.

Applications

- Stretch Base is applied to print base.
- It is applied under paints to increase elasticity.
- Before use, please stir Stretch Base well.
- Do not use any additives that are not advised.
- Its curing time is at 160-170 °C; 1,5- 2 mins or 140 – 150 °C; 2 – 2,5 mins.

Usage

- It provides to print with the silk-screen that are made between 43-62 mesh.
- It should be used with 50 – 60 Shore, U type.

Storage & Shelf Life

- Keep containers dry and tightly closed. Store in a ventilated place between (+5)-(+30)°C /(+41)-(+86)°F of temperature.
- It should be consumed within 2 years after the production date.

Technical Details



Appearance
Paste



Odor
Characteristic



Color
Yellowish Transparent



Viscosity
[(77°F/25°C) sp: 7, rpm: 20 Brookfield] :
70.000 - 80.000 [mPa.s]



Density
1,0 g/cm (77°F / 25°C)



pH
7,5 – 8,0



Boiling Point
>100°C (212°F)



Solubility
Soluble in water



Explosion Hazard
Not explosive



Packaging Information
Stretch Base is packed in
5/10/20/30/60 kg blue polyethylene
cans.

Important

The technical application and information that have been given above, are designed only as using instructions. Should not be considered as a warranty for any other use. When any help or assistance is required, our technical department is ready for help.

In case of emergency, Safety Data Sheet of this product should be ready for help at the working area. The warnings are given on safety data sheet of this product is for use outside the manufacturer/ distributor to direct/indirect can not be held responsible for any loss or damage.