



## FFB 57

### General

It is a cross linker for water based products to increase all fastnesses. Provides early curing of prints and reduces the flash curing time.

### Advantages

- It does not damage the base it is added during or after the print.
- Milky appearance

### Applications

- FFB 57 is used for improve to all fastness of the printing bases.

### Usage

- FFB 57 is used into water based printing between %1-3.

### Storage & Shelf Life

- Keep containers dry and tightly closed. Store in a ventilated place between (+5)-(+30)°C /(+41)-(+86)°F of temperature.
- It should be consumed within 2 years after the production date.

### Technical Details



**Appearance**  
Liquid



**Odor**  
Characteristic



**Color**  
Milky



**Viscosity**  
[(77 °F/25°C) sp: 4, rpm: 20 Brookfield ] :  
2.300 – 3.300 [mPa.s]



**Density**  
1,02 g/cm (77°F / 25°C)



**pH**  
6,0 – 7,0



**Boiling Point**  
>100°C (212°F)



**Solubility**  
Dispersible in water



**Explosion Hazard**  
Not explosive



**Packaging Information**  
FFB 57 is packed in  
1/5/10/20/30/60 kg blue cans.

### Important

The technical application and information that have been given above, are designed only as using instructions. Should not be considered as a warranty for any other use. When any help or assistance is required, our technical department is ready for help.

In case of emergency, Safety Data Sheet of this product should be ready for help at the working area. The warnings are given on safety data sheet of this product is for use outside the manufacturer/ distributor to direct/indirect can not be held responsible for any loss or damage.