

## PPF Thinner

### General

It is a Phthalate Free and PVC free based thinner

### Advantages

- PPF Thinner prevents that blocking of printings in the silk-screen.
- PPF Thinner doesn't contain phthalate and PVC.
- Suitable to ecological standards. It is used for reduce to viscosity of printings.
- It is easily fixed on the machine.

### Applications

PPF Thinner is used for reduce to viscosity of printings.

### Usage

It is advised to add (5 %) as thinner and retarder.

### Storage & Shelf Life

- Keep containers dry and tightly closed. Store in a ventilated place between (+5)-(+30)°C /(+41)-(+86)°F of temperature.
- It should be consumed within 2 years after the production date.

## Technical Details



**Appearance**  
Paste



**Odor**  
Characteristic



**Color**  
Transparent



**Viscosity**  
[(20°C/68°F) sp: 1, rpm: 20 Brookfield ] :  
1.002 cp



**Density**  
1,0 g/cm<sup>3</sup> (25 ° C/77 °F)



**pH**  
.



**Boiling Point**  
>100°C (212°F)



**Solubility**  
Dispersible in water



**Flash Point**  
> 374°F (190°C)



**Packaging Information**  
PPF Thinner is packed in  
1/5/10 kg cans

## Important

The technical application and information that have been given above, are designed only as using instructions. Should not be considered as a warranty for any other use. When any help or assistance is required, our technical department is ready for help.

In case of emergency, Safety Data Sheet of this product should be ready for help at the working area. The warnings are given on safety data sheet of this product is for use outside the manufacturer/ distributor to direct/indirect can not be held responsible for any loss or damage.