

# **PPF Thickener**

#### General

PVC and Phthalate free, synthetic thickener

#### **Advantages**

- PPF Thickener viscosity capability is perfect even if small quantities therefore it should be tried in pastes.
- It protects to alive of pigments. Suitable to ecological standards.

### **Applications**

- Before usage, please stir the product well.
  Do not use any additives that are not advised.
- Never use water to reduce the viscosity. After using, the silk-screen should be cleaned with water.

#### Usage

 PPF Thickener provides to raise of viscosity of print paste.

## Storage & Shelf Life

- Keep containers dry and tightly closed. Store in a ventilated place between (+5)-(+30)°C /(+41)-(+86)°F of temperature.
- It should be consumed within 2 years after the production date.



## **Technical Details**



**Appearance** Powder



**Odor** Characteristic



**Color** White



Viscosity

N/A



Density

1,0 g/cm<sup>3</sup> (77°F/25°C)



**pH** N/A



**Boiling Point** 



Solubility

Non-Dispersible in water



**Explosion Hazard** It is not explosive



**Packaging Information** 

PPF Thickener is packed in 1/5/10/20/25/30/60 kg blue polyethylene cans.

### **Important**

The technical application and information that have been given above, are designed only as using instructions. Should not be considered as a warranty for any other use. When any help or assistance is required, our technical department is ready for help.

In case of emergency, Safety Data Sheet of this product should be ready for help at the working area. The warnings are given on safety data sheet of this product is for use outside the manufacturer/ distributor to direct/indirect can not be held responsible for any loss or damage.

Rev. DATE: September 2021

**Rev. No:** 04

**TDS No:** 170 Page 1/1