

PF Low Bleed White

General

It is a Phthalate Free printing base used to achieve an elastic, soft touching and white covering effect in textile printing.

Advantages

- PF Low Bleed White is a plastisol white "low bleed" very opaque and creamy viscosity
- PF Low Bleed White provides for white covering alive effect and elastic.
- If used correctly as advised, It does not dry during the print and block in the silk-screen.
- PF Low Bleed White is phthalate free. However, it is not suitable to ecological standards due to containing PVC.

Applications

- PF Low Bleed White is used for white covering alive effect on surface.
- PF Low Bleed White works on cotton and poly cotton blend fabrics.
- Its curing time is at 320°F / 160°C; 1,5 mins.

Usage

- Fluorescent colors can be used to make alive colors
- It can be mixed with Nanoflex PF pigments. It is advised to print with the silk-screens that are made between 43-120 mesh (110-305 inch).
- 60 80 Shore, V type dr. blade should be used.
- Before usage, please stir this product well. Do not use any additives that are not advised.
 After using, the screen should be cleaned with the synthetic thinner.

Storage & Shelf Life

- Keep containers dry and tightly closed. Store in a ventilated place between (+5)-(+30)°C /(+41)-(+86)°F of temperature.
- It should be consumed within 2 years after the production date.



TECHNICAL DATA SHEET

Technical Details



Appearance Paste

Characteristic

\

Odor



White

Viscosity

[(77 °F) sp: 96, rpm: 2 Brookfield]: 1.900.000 - 2.000.000 [mPa.s]



Density

1,45 g/cm³ (77°F)



pH N/A



Boiling Point

>100 °C (212 °F)



Solubility N/A



Explosion Hazard

It is not explosive



Packaging Information

PF Low Bleed White is packed in 1/5/10/20/25/30/60 kg plastic cans.

Important

The technical application and information that have been given above, are designed only as using instructions. Should not be considered as a warranty for any other use. When any help or assistance is required, our technical department is ready for help.

In case of emergency, Safety Data Sheet of this product should be ready for help at the working area. The warnings are given on safety data sheet of this product is for use outside the manufacturer/ distributor to direct/indirect can not be held responsible for any loss or damage.

Rev. DATE: August 2021

Rev. No: 03

TDS No: 182 Page 1/1