

PF Thinner

General

It is a phthalate free based thinner.

Advantages

- PF Thinner prevents that blocking of printings in the silk-screen.
- It is easily fixed on the machine It is phthalate free.
- It is used for reduce to viscosity of printings.
- However, it is not suitable to ecological standards because it contains PVC.

Applications

PF Thinner is used for reduce to viscosity of printings.

Usage

It is advised to add (5 %) as thinner and retarder.

Storage & Shelf Life

- Keep containers dry and tightly closed. Store in a ventilated place between (+5)-(+30)°C /(+41)-(+86)°F of temperature.
- It should be consumed within 2 years after the production date.

Technical Details



Appearance
Liquid



Odor
Characteristic



Color
Transparent



Viscosity
[(77 °F) sp: 1, rpm: 20 Brookfield] :
25 – 75 [mPa.s]



Density
1,0 g/cm³ (77 °F/25°C)



pH
.



Boiling Point
>212°F



Solubility
Dispersible in water



Flash Point
> 374 °F



Packaging Information
PF Thinner is packed in
1/5/10/20/25/30/60 kg plastic cans

Important

The technical application and information that have been given above, are designed only as using instructions. Should not be considered as a warranty for any other use. When any help or assistance is required, our technical department is ready for help.

In case of emergency, Safety Data Sheet of this product should be ready for help at the working area. The warnings are given on safety data sheet of this product is for use outside the manufacturer/ distributor to direct/indirect can not be held responsible for any loss or damage.